34668-PCT USA

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/936932

CONCERNING A FILING UNDER 35 U.S.C. 371 INTERNATIONAL APPLICATION NO.

PCT/GB00/01029

INTERNATIONAL FILING DATE 20 March 2000

PRIORITY DATE CLAIMED 19 March 1999

TITLE OF INVENTION

DWWIL

LIQI	LIQUID DISPENSING APPARATUS							
	APPLICANT(S) FOR DO/EO/US HAGERLID, Peter; EHRING, Hanno; and EKSTROM, Bjorn							
ПАС	rekl.	AD, Leiel; Eliking, Mahho; ahu Eksekoni, Djofh						
Appli	cant h	nerewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:						
1.	\boxtimes	This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.						
2.		This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.						
3.		This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include itens (5), (6), (9) and (24) indicated below.						
4.	\boxtimes	The US has been elected by the expiration of 19 months from the priority date (Article 31).						
5.	\boxtimes	A copy of the International Application as filed (35 U.S.C. 371 (c) (2))						
		a. 🛛 is attached hereto (required only if not communicated by the International Bureau).						
1		b. has been communicated by the International Bureau.						
[c. \Box is not required, as the application was filed in the United States Receiving Office (RO/US).						
6.		An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).						
1		a. is attached hereto.						
1		b. has been previously submitted under 35 U.S.C. 154(d)(4).						
7.	\boxtimes	Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))						
1		a. are attached hereto (required only if not communicated by the International Bureau).						
l		b. have been communicated by the International Bureau.						
1		c. have not been made; however, the time limit for making such amendments has NOT expired.						
	_	d. A have not been made and will not be made.						
8.		An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).						
9. 18		An each or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).						
10.		An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).						
11.		A copy of the International Preliminary Examination Report (PCT/IPEA/409).						
12.		A copy of the International Search Report (PCT/ISA/210).						
	_	13 to 20 below concern document(s) or information included:						
13.		An Information Disclosure Statement under 37 CFR 1.97 and 1.98.						
14.		An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.						
15.		A FIRST preliminary amendment.						
16.		A SECOND or SUBSEQUENT preliminary amendment.						
17.		A substitute specification.						
18.		A change of power of attorney and/or address letter. A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.						
19.		A second copy of the published international application under 35 U.S.C. 154(d)(4).						
20.		A second copy of the English language translation of the international application under 35 U.S.C. 134(d)(4).						
21.								
22.		Certificate of Mailing by Express Mail Other items or information:						
23.	Z	Form PCT/IB/308, a postcard and a check in the amount of \$1,372.						
		201111 2 0 X 1 201 10 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1						
		Express Mail No. EF321682170US Date of Deposit: September 19, 2001						

4	U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR OF PCT/GB00/01029						ATTORNEY'S DOCKET NUMBER 34668-PCT USA								
¥	24.					submitted:.						CA	LCULATIONS		
	BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO							000.00	CAI	CCULATION	5 PI	O USE ONLY			
	 ✓ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO											•			
		Internat and all o	ional claim	s satisfi	ed provi	mination fee (3 sions of PCT A	rticle 33(1))-(4)			100.00	<u> </u>			
						APPROPR							\$860.00		
	months	from th	30.0 e ear	o for fulliest cla	imed pri	the oath or decority date (37 (CFR 1.492	(e)).	□ 20		30	<u>_</u>	\$0.00		
		AIMS				ER FILED	NU	MBER EXT	'RA	RA			01/2 00		
	Total c	laims ndent cla			29 4	- 20 = - 3 =	-	9			0.00		\$162.00 \$80.00		
				Claime		if applicable).	ــــــــــــــــــــــــــــــــــــــ			A \$6		 	\$270.00		
	iviuitip:	ie Depei.	ident	Cianins		TOTAL O	F ABOV	Æ CALO	CULAT			-	\$1,372.00		
		pplicant duced b				tatus. (See 37 C							\$0.00		
									SUB'	ГОТА	L =		\$1,372.00		
	Process months	sing fee	of \$1: e ear	30.00 f	or furnis imed pri	hing the English ority date (37 (translation	n later than (f)).	□ 20		30 +		\$0.00		
							TOT	AL NAT	IONAL	FEE		_	\$1,372.00		
ent e	Fee for	recording	ng the	enclos appropr	sed assignate cover	nment (37 CFR er sheet (37 CFF							\$0.00		
								L FEES) =		\$1,372.00		
nija												Amo	ount to be: refunded	\$	
- Marin													charged	\$	
	a.	×	A ch	eck in t	he amou	nt of \$1,3°	72.00	to cover the	above fee	s is encle	sed.				
Theres.	b.		Pleas	e charg	e my De	eposit Account 1 this sheet is enc	No		in the am				to cover t	he abo	ove fees.
!	c.				ssioner i	s hereby authori		rge any addi duplicate co					, or credit any	overp	ayment
	d.					ed to a credit car									038.
						ne limit under . granted to rest					t, a petit	ion to	revive (37 CF	R	
	ì ì	, , ,	,		DENCE				_	/	, `	n. 7	n /	,	
										OCN	TIDE	<u>n. /</u>	nae Levr		
	i	M. Mac		•						V.	TORE				
		ER BOT ckefelle							ł	Janet	M. Ma	cLeo	d		
		York, N			28					NAM	3		-		
										35,26					
										REGI	STRATIO	IN NC	JMBER		
										19 Se	ptembe	r 200	1		
	•									DATE					

L. 1 ķ.≓ı - 13 -

A cassette comprising a plurality of cartridges for dispensing drops of liquid in the range 10 - 500 nl therefrom, each cartridge comprising a liquid reservoir and an outlet member mounted so as to close an opening in the liquid reservoir at one end thereof, said outlet member providing an outlet port through which said liquid can be forced by a pulse of pressurised gas applied to the liquid at the other end of the liquid reservoir, thereby forming a said drop.

10

- A cassette as claimed in claim 1 wherein at least the liquid reservoirs of said cartridges are formed integrally with one another.
- A cassette as claimed in claim 1 or 2 wherein said 15 outlet port comprises an aperture in said outlet member.
 - A cassette as claimed in claim 1 or 2 wherein said outlet port comprises a protruding nozzle.

20

25

30

35

- A liquid dispensing apparatus comprising a liquid 5. reservoir, an outlet port and driving means for forcing liquid through said outlet port, said driving means comprising means for generating a pulse of gas which impinges upon liquid in the reservoir so as to force liquid through the outlat port.
- An apparatus as claimed in claim 5, wherein said outlet port is formed integrally with the or each liquid reservoir.
 - An apparatus as claimed in claim 5 wherein said outlet port is provided by a separate outler member which is mounted so as to close an opening in the liquid reservoir.

25-04-2001 FED 11:01 FAX 01273 244244 F.B.DEEN

+++ EPO MUNIC GB 000001029

- 13a -

8. An apparatus as claimed in claims 5, 5 or 7 wherein said outlet port and liquid reservoir are moulded from

INDALA . DILA GIS

JC16 Rec'd PCT/PTO SEP 1 9 2001 PCT/GB00/01029

WO 00/56455

5

10

15

20

25

30

35

2/12/17 -1-

Liquid Dispensing Apparatus

This invention relates to liquid dispensing apparatus and in particular to liquid dispensing apparatus which are able to dispense small volumes of liquid.

In certain applications it is desirable to be able to dispense very small volumes of liquid from a container, for example in the range 10-500 nanolitres (nl). Drops of this size cannot normally be produced by pumping liquid out of a capillary since surface tension will hold the drop to the tip of the capillary until it is sufficiently large that its weight overcomes this surface tension. This does not happen until the volume of the drop is of the order of 10 to 50 microlitres - i.e. 2 to 3 orders of magnitude greater than the range of interest.

Devices are available which overcome this limitation by forcing a measured amount of liquid through the tip of a nozzle using a piezo-electric actuator acting on the liquid. However such systems are expensive and may only be used with a single type of liquid at a time - thus multiplying the cost where several different liquids need to be dispensed.

It is an object of the present invention to provide an improved apparatus and when viewed from a first aspect the invention provides a liquid dispensing apparatus comprising a liquid reservoir, an outlet port and driving means for forcing liquid through said outlet port, said driving means comprising means for generating a pulse of gas which impinges upon liquid in the reservoir so as to force liquid through the outlet port.

Thus it will be seen that in accordance with the invention liquid may be dispensed by forcing it through the outlet port by means of a pulse of gas. The volume of liquid dispensed may be controlled by adjusting the

WO 00/5645\$

5

10

15

20

25

30

35

PCT/GB00/01029

- 2 -

amplitude and duration of the gas pulse. It has been found that this enables accurate control of the volume dispersed, down to the order of 50-500 nl in the preferred embodiment. Furthermore as a gas is used as the medium for transmitting force to the liquid, it is not necessary for any part of the driving means to be in contact with the liquid to be dispensed. This has clear advantages both from the point of view of preventing contamination of the liquid and also the raduced necessity to clean the apparatus.

As the driving impulse is applied to liquid in the reservoir, it is not necessary to have any part of the driving means arranged in the vicinity of the outlet port. This means that the outlet port can be simple to manufacture and the outlet port may even be provided on a disposable member.

In one preferred arrangement in accordance with the invention, the outlet port is an integral part of the apparatus. In a particularly preferred embodiment one or both of the outlet port and the liquid reservoir are moulded from a suitable plastics material, thereby allowing them to be made disposable. More preferably the outlet port and liquid reservoir are both moulded from suitable plastics, most preferably integrally with each other, to form a cartridge. Alternatively such a cartridge could be made from one or more other suitable materials such as silica or stainless steel.

Cartridges of the kind described above may be provided singly, but preferably a plurality are provided in a cassette. Such an arrangement is novel and advantageous in itself and thus when viewed from a second aspect the present invention provides a cassette comprising a plurality of cartridges for dispensing liquid therefrom, each cartridge comprising an outlet port in the form of a protruding nozzle and a liquid reservoir integrally formed therewith.

Preferably the cartridges are formed integrally

5

10

15

20

25

30

35

~ 3 -

with one another to form said cassette.

The invention makes it possible, at least in some preferred embodiments, to provide cartridges pre-filled with the necessary liquid and having the required outlet port formed integrally therewith. All that is necessary then is simply to place the liquid reservoir of the cartridge or each certridge of a cassette of cartridges in gaseous communication with a means to generate gas pulses, in order to form a liquid dispensing apparatus in accordance with the first aspect of the invention. This is extremely convenient to a user who thus does not need to be concerned with filling reservoirs with liquid, cleaning the outlet port etc. Indeed in at least preferred embodiments of this aspect of the invention, contact with the liquid to be dispensed may be completely avoided.

In other preferred arrangements the outlet port is provided by a separate outlet member which is mounted so as to close an opening in the liquid reservoir. This is advantageous since it allows the liquid reservoir and outlet member to be made from different materials each of which can be optimised for its function. For example, the dimensions of the liquid reservoir may be relatively uncritical and so it could be made relatively inexpensively, e.g. as an injection moulded plastics component. On the other hand, the dimensions of the outlet port of the outlet member are likely to be more critical and it might for example by made to a tighter tolerance, e.g. from metal.

As above, the outlet member and liquid reservoir preferably together form a cartridge, and in preferred embodiments a cassette comprising a plurality of such cartridges is provided. Thus when viewed from a further aspect the present invention provides a cassette comprising a plurality of cartridges for dispensing liquid therefrom, each cartridge comprising a liquid reservoir and an outlet member mounted so as to close an

5

10

15

20

25

30

35

PCT/GB00/01029

-4.

opening in the liquid reservoir, said outlet member providing an outlet port through which said liquid can be forced by a pulse of pressurised gas.

preferably at least the liquid reservoirs of said cartridges are formed integrally with one another to form said cassette.

In some preferred embodiments the outlet port comprises a protruding nozzle, e.g. a capillary tube. The bore of such a nozzle is preferably within the range 0.05 to 0.2 mm, most preferably about 0.1 mm. The length of the nozzle is preferably in the range 1 to 15 mm, most preferably 5 mm.

More preferably, the outlet port comprises an aperture in a wall of the liquid reservoir. The aperture is chosen in size to give the required volume of drop when a given pressure pulse is applied. The aperture however should be small enough that the surface tension in the liquid in the reservoir prevents it from leaking through.

In accordance with the first and second aspects of the invention, the wall of the liquid reservoir in which the aperture is provided may be integral with the reservoir but preferably it is a separate wall member mounted so as to close an opening in the liquid reservoir.

Where, as is preferred, a plurality of cartridges together form a cassette, each may have its own such wall member or two or more of the cartridges may share a wall member with an aperture for each cartridge.

A single aperture may be provided for the or each liquid reservoir, or more may be provided to increase the volume that may be dispensed without increasing the size of the aperture (which could give rise to a greater probability of leaking).

The aperture could be any shape, but most conveniently it is round. However, if larger volumes of liquid are required an elongate slit could for example

5

10

15

20

25

30

35

PCT/GB00/01029

- 5 -

by employed.

In preferred embodiments the aperture is between 2 and 300 micrometers wide, preferably approximately 40 micrometers. If the aperture is a slit it could for example be 40×500 micrometers.

The wall member could be made from any suitable material, e.g. plastics, metal, glass or ceramics. Preferably it has the opposite relationship to water as the liquid for which it is intended to be used, i.e. preferably the member is hydrophilic if the liquid is hydrophobic and vice versa. It may have any suitable thickness, but preferably it is between 10 micrometers and 1000 micrometers (1 mm), most preferably approximately 50 micrometers.

The aperture may be formed by suitably precise technique e.g. etching, electroplating, laser drilling or mechanical drilling.

The wall member may be fixed to the or each liquid reservoir in any suitable manner e.g. gluing, ultrasonic welding, friction welding etc. In one preferred embodiment the liquid reservoir tapers towards its open end and the wall member is pressed into an interference fit with the tapered end. The wall member therefore preferably has the same peripheral shape as the liquid reservoir, most preferably this being round. The diameter of the wall member in such a case is preferably between 0.5 and 6 mm, most preferably approximately 2

The cartridge or each cartridge of a cassette may be filled with a suitable liquid prior to use, e.g. a lyophilised reagent which is dissolved in water when required. The preferred embodiments of the invention in which the liquid reservoir is adjacent the outlet port are advantageous in this context since just the required amount of reagent can be made up as required without extra being required to accommodate dead space in pipes etc.

5

10

15

20

25

30

35

PCT/GB00/01020

- 6 -

Cassettes of cartridges in accordance with the invention as described above are useful in many applications including but not limited to immuno assays, cell assay, drug screening and they are particularly useful for sequencing DNA using the method often referred to as "Sequencing Ey Synthesis" as they allow for example a cassette having cartridges containing each of the four nucleotides required for DNA sequencing. Preferably therefore the cartridges respectively contain one or more nucleotides. The ability to provide a plurality of cartridges in a single cassette further allows a complete set of reagents required for a sequencing programme to be provided. Thus preferably further cartridges of the cassette respectively contain one or more enzymes, more preferably selected from a group comprising polymerase, luciferase, adenosine triphosphate (ATP) sulfurylase, and a nucleotidedegrading enzyme such as apyrase. Such a set of reagents is particularly useful for the method of genetic sequencing set out in WO 98/13523. will be appreciated that the invention extends to a method of genetic sequencing using a liquid dispensing apparatus or cassette as herein described.

As discussed above, cartridges of the kind described above may be filled by a user with the appropriate liquid as required. Alternatively the cartridge or each cartridge of a cassette is pre-filled with the appropriate liquid and sealed, the seal being broken upon mounting the cartridge into an apparatus which includes the gas pulse generation means. Preferably the seal is broken by the action of mounting the cartridge into the apparatus. Advantageously a conduit for establishing gaseous communication with the interior of the liquid reservoir of the cartridge breaks the seal.

It will be seen from the above that a sealed cartridge containing a liquid to be dispensed by means

10

15

20

25

30

35

PCT/GB00/01029

- 7 -

of apparatus in accordance with the first aspect of the invention is in itself not only novel, but particularly convenient for a user and thus when viewed from a further aspect the present invention provides a cartridge comprising a liquid reservoir having a predetermined liquid received therein, said reservoir being closed at one end thereof by frangible sealing means, and an outlet port attached to or integrally formed with said reservoir and in fluid communication therewith.

As an alternative it will be seen that the invention extends to a cartridge for use in a liquid dispensing apparatus as hereinbefore described comprising a liquid reservoir, and an outlet port attached to or integrally formed with said reservoir and in fluid communication therewith, in combination with a reagent, preferably a nucleotide or enzyme.

The reagent e.g. nucleotide or enzyme could be in a suitable liquid form or could be lyophilised. In the latter case a readily available diluent such as water could be used, or a suitable diluent could instead also be provided as part of the combination.

The frangible sealing means preferably comprises a foil membrane e.g. of aluminium covering an opening onto the reservoir. This is a cost-effective way of retaining liquid in the reservoir without it becoming contaminated, whilst at the same time being relatively easy to pierce - e.g. by a gas nozzle associated with the gas pulse generation means.

The predetermined liquid preferably comprises a nucleotide or an enzyme.

Where an enzyme is provided, either as the predetermined liquid in a pre-filled cartridge or as a separate reagent to be added by a user, the enzyme is preferably selected from a group comprising polymerase, luciferase, adenosine triphosphate (ATP) sulfurylase, and a nucleotide-degrading enzyme such as apyrase.

10

15

20

25

30

35

0/56455 PCT/GB00/01029

~ 8 -

The means for generating the gas pulses may comprise any suitable means - e.g. a bellows arranged to undergo a rapid reduction in volume. Preferably however the pulse generation means comprises a source of pressurised gas which may be selectively placed into communication with the liquid reservoir. Such arrangements are especially beneficial since a single source of pressurised gas may be used to drive a plurality of liquid reservoirs, thereby giving a significant saving in cost over arrangements where driving means are individually provided for each of a number of nozzles. Means for selectively placing the liquid reservoir into communication with the source of gas may be provided for each of such liquid reservoirs or two or more of them may be associated with a single selection means so that their contents are dispensed simultaneously.

Preferably one or more valves is provided to effect said selective communication and in the preferred embodiment an electromagnetic valve is used. This is particularly advantageous since electromagnetic valves can be operated very quickly and accurately with little mechanical wear.

Where, as is preferred, the apparatus for dispensing liquid comprises gas pulse generation means in the form of means for selectively communicating a source of pressurised gas with the liquid reservoir, the source of pressurised gas may be comprised within the apparatus. Most preferably the source of pressurised gas comprises a compressor supplying a pressure reservoir. Alternatively, the apparatus may comprise a gas inlet for connection to an external source of pressurised gas. In either case the apparatus of the invention preferably comprises means to regulate the pressure of the incoming gas thereby allowing the amplitude of the pulses generated to be accurately controlled and thus the volume of liquid to be

5

10

15

20

25

30

35

PCT/GB00/01029

- 9 -

accurately controlled as a consequence. The pressure regulation means may comprise a mechanical release valve or the like. Preferably however such means comprises an electronic pressure sensor which is used to monitor the pressure in the reservoir or gas inlet and means for increasing or decreasing said pressure in response to the signal from the pressure sensor to maintain the pressure within a predetermined range.

The gas pulse generation means preferably generates pressure pulses having an amplitude in the range 200 to 1000 millibers, with a pulse width in the range 1-1000 milliseconds. This enables volumes in the range 50 nl to 10000 nl $(10\mu l)$ to be dispensed.

Certain preferred embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings in which:-

Figure 1 is a schematic view of a cassette of cartridges and liquid dispensing apparatus in accordance with the invention; and

Figure 2 is a cross-section through a cartridge in accordance with a second embodiment of the invention.

Turning to Figure 1 there may be seen a liquid dispensing apparatus comprising a cartridge cassette designated generally by the reference numeral 1. This cassette contains eight cartridges 2, three of which are visible in the drawing. Each cartridge 2 is partly filled with a reagent 4 used for genetic sequencing. The volume of the cartridges is approximately 2 ml. Different reagents 4 are provided in each cartridge 2. Specifically, four of the cartridges 2 contain the deoxynucleotide triphosphate of one each of the four bases cytosine, guanine, adenosine and thymine. Four further cartridges 2 contain polymerase, luciferase, apyrase and ATP sulfurylase. Equally however some or all of the cartridges could have the same contents.

At the end of each cartridge 2 there is a capillary nozzle 6. This nozzle has a bore of 0.1 mm. In the

10

15

20

25

30

35

WO 00/56455 PCT/GB00/01029

- 10 -

depicted embodiment the nozzle 6 is integrally moulded with the rest of the cartridge 2 from a polymer. However the cartridge could be formed with means to receive a separate nozzle.

The cassette 1 has an outer case 8 which protects the cartridges 2 from contamination by the user handling them and conversely protects the user from having to come into contact with the liquid being dispensed or the very fine, i.e. sharp nozzles 6. Apertures 10 are provided in the base of the cassette casing 8 which are aligned with the nozzles 6 to allow the liquid through.

At the upper end of the cassette 1 a thin metal foil 16 is provided over the tops of the cartridges 2 to seal them. The foil 16 extends across the open upper end of the cassette 1 formed by the side walls of the casing 8, but slightly downwardly set from the top edge so as to leave un upstanding lip around the top of the foil 16.

The cassette 1 is installed in a carriage 18 which can be moved laterally in both directions over a Micro Titre Plate (MTP) 12. The MTP has 96 wells 14, three of which are shown. The cassette 1 is actually received in a downwardly tapering chamber 20, so as to rest on an apertured plate 22, the apertures of which are in alignment with the apertures 10 in the cassette and, when the carriage 18 is properly positioned, also with the wells 14 of the MTP 12.

The cassette 1 is retained in the chamber 20 by means of a hinged lid 3, having a rubber seal 24 on its underside which is a tight fit inside the lip at the top edge of cassette casing 8. The seal 24 is arranged also to ensure that the cartridges 2 are sealed with respect to one another as well as with respect to the lid 3.

Mounted in the lid 3 is an array of punching cannulae 28, one for each of the cartridges 2. These cannulae 28 have sharp tips and so as the lid 3 is hinged downwardly onto the cassette 1 in the chamber 20,

5

10

15

20

25

30

35

PCT/GB00/01029

- 11 -

the cannulae 28 pierce the foil seal 28. The other ends of the cannulae are each connected by means of a pipe 26 to an electromagnetic valve (not shown) which selectively connects the pipe 26 to a source of pressurised gas for a predetermined time to produce a pulse of gas. The pressurised gas is generated by a compressor type EC Genius/M 202 2305 EU.SV.C which is commercially available from Fini, Zola, Predosa, Bo-Italy.

The pulse of gas forces a measured amount of reagent 4 out of the cartridge 2, through the nozzle 6 and into the corresponding well 14 on the MTP 12. A 500 millibar pulse, for 10 milliseconds dispenses approximately 200 nanolitres of reagent into the well 14. Reagent is only dispensed from one of the cartridges 2 at a time although simultaneous dispensing is also possible and this could be useful e.g. where a plate having a greater number of wells was used with an interleaved series of wells used so that dispensing into the wells of several distinct series can be carried out without moving the carriage 18.

Once the reagents in the cartridges have been used, the cassette may simply be removed by opening the lid 3 and replaced with a new one, the fresh seals being broken by the cannulae 28. Since neither the cannulae 28 nor any other permanent part of the apparatus comes into contact with the reagents at any stage, there is little chance of contamination and it is not necessary to clean the apparatus between uses, even if different reagents are being used.

Figure 2 shows part of the cartridge 30 of another embodiment of the invention. It will be seen that the liquid reservoir 32 tapers at its lower end 32a to form an opening circumscribed by an annular lip 34. The reservoir 32 and lip 34 are integrally formed in injection moulded plastics. The bottom opening is closed by a thin metallic foil disc 36 which has a central

10

15

20

PCT/GB00/01029

- 12 -

aperture drilled into it. The disc 36 is pressed into the end of the liquid reservoir 32 thereby forming a fluid-tight interference fit. The disc is 2 mm in diameter and 50 micrometers thick. The aperture is essentially circular with a diameter of approximately 40 micrometers. This is sufficiently small to prevent any leakage of liquid from the reservoir 32.

This embodiment operates in exactly the same way as the embodiment already described, although it will be appreciated that it has the additional benefits that the size of the aperture is easier to control precisely than is the bore of the capillary tube, and furthermore there is no potentially hazardous sharp tip.

Although embodiments of the invention having a casette comprising several cartridges have been described, it will be understood by those skilled in the art that the invention is not limited to using several cartridges and that a single cartridge reservoir could be used instead. Furthermore, the liquid reservoir need not be removable and could instead be an integral part of the apparatus.

5

30

35

PCT/GB00/01029

- 13 -

Claims:

- 1. A cassette comprising a plurality of cartridges for dispensing liquid therefrom, each cartridge comprising a liquid reservoir and an outlet member mounted so as to close an opening in the liquid reservoir, said outlet member providing an outlet port through which said liquid can be forced by a phlse of pressurised gas.
- 2. A cassette as claimed in claim 1 wherein at least the liquid reservoirs of said cartridges are formed integrally with one another.
- A cassette as claimed in claim 1 or 2 wherein said
 outlet port comprises an aperture in said outlet member.
 - 4. A cassette as claimed in claim 1 or 2 wherein said outlet port comprises a protruding nozzle.
- 5. A liquid dispensing apparatus comprising a liquid reservoir, an outlet port and driving means for forcing liquid through said outlet port, said driving means comprising means for generating a pulse of gas which impinges upon liquid in the reservoir so as to force liquid through the outlet port.
 - 6. An apparatus as claimed in claim 5, wherein said outlet port is formed integrally with the or each liquid reservoir.
 - 7. An apparatus as claimed in claim 5 wherein said outlet port is provided by a separate outlet member which is mounted so as to close an opening in the liquid reservoir.
 - 8. An apparatus as claimed in Claims 5, 6 or 7 wherein said outlet port and liquid reservoir are moulded from

DWWIEWE OLINCE

5

10

15

20

25

- 14 -

PCT/GB00/01029

plastics to form a cartridge.

9. An apparatus as claimed in claim 8 comprising a cassette, said cassette comprising a plurality of said cartridges.

- 10. An apparatus as claimed in any of claims 5 to 9 wherein the pulse generation means comprises a source of pressurised gas which may be selectively placed into communication with the liquid reservoir.
- 11. An apparatus as claimed in claim 10 wherein one or more electromagnetic valves is provided to effect said selective communication.
- 12. An apparatus as claimed in any of claims 5 to 11 wherein said gas pulse generation means is arranged to generate pulses having an amplitude in the range 200 to 1000 millipars.
- 13. An apparatus as claimed in any of claims 5 to 12 wherein said gas pulse generation means is arranged to generate pulses having a width in the range 1 to 1000 milliseconds.
 - 14. An apparatus as claimed in any of claims 5 to 13 wherein the or each cutlet port comprises a protruding nozzle.
- 30 15. A cassette or apparatus as claimed in any of claims 5 to 13 wherein said outlet port comprises an aperture in a wall of the liquid reservoir.
- 16. A cassette or apparatus as claimed in claim 3 or 15 35 wherein said aperture has a width of between 2 and 300 micrometers.

The state of the state of

WO 90/56455

PCT/GB00/01029

- 15 -

17. A cassette comprising a plurality of cartridges for dispensing liquid therefrom, each cartridge comprising an outlet port in the form of a protruding nozzle and a liquid reservoir integrally formed with the outlet port.

5

18. An apparatus or cassette as claimed in any preceding claim wherein the or each liquid reservoir contains a quantity of liquid and is closed at one end thereof by a frangible sealing means.

10

15

- 19. A cartridge comprising a liquid reservoir having a predetermined liquid received therein, said reservoir being closed at one end thereof by frangible sealing means, and a nozzle attached to or integrally formed with said reservoir and in fluid communication therewith.
- 20. An apparatus, cartridge or cassette as claimed in claim 18 or 19 wherein said frangible sealing means comprises a foil membrane.
 - 21. An apparatus, cartridge or cassette as claimed in any preceding claim wherein said liquid reservoir contains a nucleotide or enzyme.

25

30

35

- 22. An apparatus, cartridge or cassette as claimed in claim 21 wherein said liquid receiving reservoir contains an enzyme selected from a group comprising polymerase, luciferase, adenosine triphosphate (ATP) sulfurylase, and a nucleotide-degrading enzyme such as apyrase.
- 23. A liquid dispensing apparatus including a cassette or cartridge as claimed in any of claims 1 to 4 or 15 to 22.

SUBSTITUTE SHEET (RULE 26)

FIG. 1




FIG.2

Docket No. 14256

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

First Named			
Inventor	1	Peter Hagerlid	,
Appln. No.	.:	09/936,932	
Filed	:	September 19, 2001	Group Art Unit:
Title	:	LIQUID DISPENSING APPARATUS	Examiner:

DECLARATION AND POWER OF ATTORNEY FOR UTILITY PATENT APPLICATION (37 C.F.R. § 1.63)

As a below named inventor, I hereby declare that my mailing address and citizenship are as stated below.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if blural names are listed below) of the subject matter that is claimed and for which a patent is sought on the invention entitled:

and a second	of the amilest matter that is a	· · ·	•	
The state of the s	<u> </u>	PENSINGARRARA		
Number and a I hereby state that I hereby state that I hereby any amendmen	ember 19, 2001 as United Simended on (if applies are reviewed and understand to specifically referred to about the disclose information knows applications, material information, material information	ible). I the contents of the above ve. Iown to me that is material formation which became a	identified specifi to palentability a vailable between	cation, including the claims,
	priority benefits under 35 l		1.71 July 1997	unification(s) for natent or
inventor's certificate, or 365(a) States of America, listed belov certificate, or any PCT interna	of any PCT informational ap wand have also identified be	oplication which designate low, by checking the box,	d at least one cou any foreign appli	ntry other than the United cation for patent or inventor's
Prior Foreign	Country	Foreign Filing Date	Priority Not	Certified Copy Attached?
Application Number(s)		(MM/DD/YYYY)	Claimed	Yes No
9906477,6	Great Britain	03/19/99		
				· ·
	fit under 35 U.S.C. 119(e) o	f any United States provisi	ional application(
Уррпсар	on Number(s)		Titting Date (MA)	ODDITE 1.17
- 付種語は、これが、一個	the second of th	· / ·		•

I hereby claim the bonefit under 35 U.S.C.	120 of any earlier U.S./PCT application(s) list	ited below:
Application Serial No.	Filing Date	Status
		(pending, patented, ahandoned)

I hereby appoint Richard S. Clark, Reg. No. 26, 154 and Janet M. MacLeod, Reg. No. 35, 263 of the firm of Dorsey & Whitney LLP with offices at 250 Park Avenue, New York, New York 10177 as attorneys to prosecute, the patent application identified above and to transact all business in the Patent and Trademark Office connected therewith, including full power of association, substitution, and revocation.

PLEASE DIRECT ALL CORRESPONDENCE TO:

Name	Janet M. MacLeod, Esq.
Address	DORSEY & WHITNEY LLP
	250 Park Avenue New York, NY 10177
Telephone	2612-415-9200
Fax	212-953-7201

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. § 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Sole or First Invent	or:		,		
Giv	en Name (First and midd	(e)	, l	Pamily Name or Surname	• • •
	Peter		-	Hagerlid	· · · · · · · · · · · · · · · · · · ·
Inventor's Signature	1 7 1	mulal		Date: 02010#	
	Uppsala SEY	Sweden State	Zip	Citizenship: Sweden	
Post Office Address	Sköldungagatan 1, Uj	ppsala. Sweden S-753	34	1	

Second Inventor:				
Give	n Namo (First and midd	le)		Family Name or Surname
	Наппо		,	Ebring
Inventor's Signature	259	<i>\</i>		Date: Jan 7, 2002
Residence	Uppsala SEX	Sweden State	Z ip	Citizenship: Germany
Post Office Address	Karlsrogatan 83a, Up			

A THE COURT OF A STATE OF THE S				William Co Chipman
Giver	Name (First and	middle)	Fill	nily Name or Surname
	Björn			Ekström
nventor's Signature	In	ulm		Date: Jan 4, 2002
Residence	Uppsala/St	Sweden State	Zip	Citizenship: Sweden
Post Office Address	City Järovägen 27. U	Ippsala, Sweden S-256		
Ost Office 2 Roses				
ourth Inventor:				
	n Name (First and	middle)	Fa	mily Name or Surname
Inventor's			<u> </u>	Date:
Signature Résidence				Citizenship:
	City	State	Zip	1
Post Office Address				
Fifth Inventor:				
Giv	en Name (First an	d middle)	6 ·	amily Name or Surname
	. ,			2
2 1				Date:
Inventor's			~	
Signature		<u> </u>	<u>~_</u>	Citizenship:
	City	State	Zip	
Signature	city	State	Zip	
Signature Residence		State	Zip	
Signature Residence		State	Zip	
Signature Residence Post Office Address Sixth Inventor:	ven Namo (First a)	id middle)		
Signature Residence Post Office Address Sixth Inventor:	ven Namo (First a)			Citizenship:
Signature Residence Post Office Address Sixth Inventor: Giv	ven Namo (First a	nd middle)		Citizenship:
Signature Residence Post Office Address Sixth Inventor: Giv	ven Namo (First a	nd middle)		Citizenship: Family Name of Surname Date:
Signature Residence Post Office Address Signature Giventor's Signature	ven Namo (First a	nd middle)		Citizenship: Family Name or Surname Date:

CONTRACTOR			and the same of th	
Seventh Inventor:				
Ģivə	n Nume (First or	d middle)	Fai	mily Name or Surname
Inventor's Signature				Date:
Residence				Citizenship:
	City	State	Zi _P	
Post Office Address			3	
	\			
Eighth Inventor:				
, Giver	n Name (First ac	d middle)	Fai	nily Name of Surname
	-			
Inventor's Signature				Date;
Residence				Citizenship:
u nda	City	Sine	Zip	1 ~
Post Office Address)			
			and the second second	
Ninth Inventor:				
Giver	i Name (First an	d middle)	Far	nily Name or Surname
	, ,			
Inventor's Signature	·			Dute:
Population and the second				
Residence				Citizenship:
	City	Stale	Zjp	Cltizenship:
Post Office Address	City	State	Zip	Cltizenship:
Post Office Address	City	Stale	Zip	Cltizenship:
Post Office Address Tenth Inventor:				Clrizenship:
Post Office Address Tenth Inventor:	City Name (First an			Citizenship: nily Name or Surname
Post Office Address Tenth Inventor: Giver		d middle)		nily Name or Surname
Post Office Address Tenth Inventor: Giver Inventor's Signature		d middle)	Fax	nily Name or Surname
Post Office Address Tenth Inventor: Giver		d middle)	Fax	nily Name or Surname
Post Office Address Tenth Inventor: Giver Inventor's Signature		d middle)	Fax	nily Name or Surname

United States Patent & Trademark Office

Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

□ Page(s)	of		were not present
for scanning.		(Document title)	•
□ Page(s)	of		were not
present for scanning		(Dogument title)	

Scanned copy is best available. Declaration & once dack